

**CALIBRE MAKES A NEW DISCOVERY ALONG THE VTEM GOLD CORRIDOR AT THE LIMON MINE;
DRILLING AT THE PAST PRODUCING TALAVERA MINE HITS ADDITIONAL HIGH-GRADES;**

Calibre Mining News Release, September 10, 2024 - Drill Hole Table

*See notes at the bottom of the table

Drill Hole ID		From (m)	To (m)	Interval (m)	ETW (m)	Au (g/t)
LIM-24-4890		0.0	86.1	86.1		NS
		86.1	90.7	4.6		0.09
	<i>Including</i>	90.7	96.4	5.8	1.2	1.24
		93.7	95.9	2.2	0.4	2.21
		96.4	99.7	3.3		0.10
		99.7	101.2	1.5	0.3	0.38
		101.2	111.9	10.7		0.08
		111.9	112.2	0.4	0.1	1.60
		112.2	115.7	3.5		0.12
	<i>Including</i>	115.7	132.1	16.5	3.3	8.98
		119.2	120.7	1.5	0.3	14.17
		123.2	126.9	3.7	0.8	18.17
		129.0	132.1	3.1	0.7	14.12
		132.1	139.3	7.2		0.05
		139.3	140.4	1.1	0.3	1.01
	140.4	154.0	13.6		0.03	
	154.0	155.0	1.0	0.2	0.54	
LIM-24-4895		0.0	49.9	49.9		NS
		49.9	57.1	7.2		0.01
		57.1	58.4	1.4	1.34	16.52
		58.4	62.1	3.7		0.01
		62.1	103.7	41.6		NS
		103.7	104.8	1.1		0.00
		104.8	105.3	0.6	0.54	8.40
		105.3	106.3	1.0		0.01
LIM-24-4917		0.0	23.0	23.0		NS
		23.0	89.6	66.6		0.00
		89.6	94.7	5.1	5.05	0.43
		94.7	120.3	25.6		0.04
		120.3	140.9	20.7		NS
		140.9	146.7	5.8		0.03
		146.7	147.1	0.4	0.31	29.90
		147.1	172.9	25.8		0.05
		172.9	174.2	1.3	1.14	0.67
		174.2	179.5	5.3		0.03
LIM-24-4933		0.0	47.7	47.7		NS

		47.7	57.0	9.4		0.02
		57.0	75.0	18.0		NS
		75.0	77.4	2.4		0.03
		77.4	79.2	1.8	1.4	5.29
	<i>Including</i>	77.4	78.4	1.0	0.8	9.17
		79.2	89.9	10.7		0.03
		89.9	97.5	7.6	6.7	0.20
		97.5	102.1	4.6		0.01
LIM-24-4938		0.0	106.5	106.5		NS
		106.5	119.9	13.4		0.04
		119.9	121.9	2.0		0.98
		121.9	124.1	2.2		0.01
		124.1	125.3	1.2		0.43
		125.3	127.1	1.8		0.08
		127.1	137.3	10.3		4.92
	<i>Including</i>	128.1	132.9	4.9		9.79
		137.3	144.0	6.7		0.02
LIM-24-4939		0.0	12.2	12.2		NS
		12.2	20.6	8.5		0.02
		20.6	25.7	5.1	5.02	6.10
	<i>Including</i>	22.4	24.5	2.1	2.08	13.24
		25.7	34.9	9.2		0.04
		34.9	48.3	13.5		NS
		48.3	69.6	21.3		0.02
LIM-24-4937		0.0	15.6	15.6		0.01
		15.6	16.6	1.0		0.49
		16.6	31.1	14.5		0.04
		31.1	37.0	5.9	1.42	0.97
		37.0	45.8	8.8		0.02
		45.8	46.3	0.5	0.11	1.32
		46.3	49.3	3.0		0.01
		49.3	49.8	0.6	0.12	4.06
		49.8	73.0	23.2		0.04
		73.0	90.4	17.4		NS
		90.4	92.9	2.5		0.03
		92.9	95.5	2.6	0.6	0.76
		95.5	100.2	4.8		0.04
		100.2	120.5	20.3		NS
		120.5	125.2	4.7		0.05
		125.2	127.3	2.1	0.49	3.78
		127.3	128.3	1.0		0.01
		128.3	157.1	28.8		NS
		157.1	167.9	10.8		0.06

		167.9	225.3	57.4		NS
		225.3	233.1	7.9		0.06
		233.1	248.0	14.9		NS
		248.0	249.5	1.5	0.35	0.35
		249.5	275.0	25.5		0.03
		275.0	278.2	3.2	2.79	8.79
	<i>Including</i>	275.0	276.6	1.6	1.38	15.98
		278.2	293.7	15.6		0.01
LIM-24-4953		0	23.3	23.3		0.03
		23.3	24	0.7		0.64
		24	47.4	23.4		0.04
		47.4	48.75	1.35		0.28
		48.75	65.65	16.9		0.08
		65.65	66	0.35		1.29
		66	71.1	5.1		0.03
		71.1	72.5	1.4		0.83
		72.5	84.4	11.9		0.03
		84.4	85.95	1.55		1.74
		85.95	101.8	15.85		0.05
		101.8	102.45	0.65		0.78
		102.45	110.15	7.7		0.11
		110.15	111.05	0.9		0.49
		111.05	119.35	8.3		0.07
		119.35	120.3	0.95		0.40
		120.3	179.25	58.95		0.02
		179.25	179.85	0.6		0.96
		179.85	207	27.15		0.03
		207	207.65	0.65		0.22
		207.65	211.4	3.75		2.53
	<i>Including</i>	211	211.4	0.4		19.95
		211.4	214.25	2.85		0.04
		214.25	215.7	1.45		0.97
		215.7	221.4	5.7		0.21
		221.4	234.95	13.55		1.21
	<i>Including</i>	223.75	224.6	0.85		5.67
		234.95	244.4	9.45		0.07
		244.4	244.9	0.5		3.06
		244.9	266.3	21.4		0.04
		266.3	266.8	0.5		0.84
		266.8	275.9	9.1		0.05
		275.9	276.8	0.9		1.47
		276.8	280.2	3.4		0.04
		280.2	281.3	1.1		2.89

		281.3	293.3	12		0.07
		293.3	294.4	1.1		0.58
		294.4	298.95	4.55		0.04
		298.95	299.55	0.6		0.67
		299.55	319.25	19.7		0.10
		319.25	321.95	2.7		1.12
		321.95	333.25	11.3		0.09
		333.25	335.25	2		0.51
		335.25	358.9	23.65		0.09
		358.9	359.4	0.5		4.26
		359.4	374.6	15.2		0.04
		374.6	403	28.4		NS
		403	404.65	1.65		0.03
		404.65	405.85	1.2		1.30
		405.85	408.2	2.35		0.07
		408.2	410.7	2.5		0.64
		410.7	414.9	4.2		0.12
		414.9	416.1	1.2		38.87
		416.1	427.7	11.6		0.03
		427.7	430.6	2.9		0.48
		430.6	435	4.4		0.05
		435	438.95	3.95		1.16
		438.95	466.2	27.25		0.03
		466.2	467.95	1.75		1.34
		467.95	472.25	4.3		0.05
		472.25	473.2	0.95		0.92
		473.2	489.15	15.95		0.02
		489.15	489.7	0.55		1.52
		489.7	510.65	20.95		0.04
		510.65	512	1.35		0.63
		512	534	22		0.05
		534	534.6	0.6		1.94
		534.6	538.9	4.3		0.02
		538.9	539.8	0.9		1.21
		539.8	555.35	15.55		0.02
LIM-24-4943		0.0	28.1	28.1		NS
		28.1	68.6	40.5		0.00
		68.6	103.7	35.1		NS
		103.7	134.9	31.2		0.00
		134.9	147.9	13.1		NS
		147.9	274.2	126.3		0.01
		274.2	284.6	10.5		6.38
	<i>Including</i>	274.2	277.6	3.4		8.12

		281.9	282.9	1.1		9.44
		284.6	369.4	84.8		0.10
		369.4	378.5	9.2		1.86
	<i>Including</i>	372.6	376.5	3.9		3.12
		378.5	380.7	2.2		0.07
		380.7	413.3	32.6		NS
		413.3	449.9	36.6		0.02
LIM-24-4945		0.0	37.1	37.1		NS
		37.1	38.1	1.0		0.02
		38.1	39.1	1.0	0.72	1.21
		39.1	65.3	26.2		0.02
		65.3	66.4	1.1	0.74	0.84
		66.4	96.6	30.2		0.02
		96.6	155.7	59.1		NS
		155.7	156.6	0.9	0.58	0.79
		156.6	203.4	46.8		0.03
		203.4	203.9	0.5	0.32	1.05
		203.9	254.0	50.2		0.01
		254.0	254.5	0.5	0.32	0.95
		254.5	259.1	4.6		0.03
		259.1	274.0	14.9		NS
		274.0	286.0	12.0		0.01
		286.0	288.6	2.6	0.44	0.49
		288.6	299.5	10.9		NS
		299.5	306.0	6.5	3.84	19.81
	<i>including</i>	301.5	303.0	1.6	0.94	52.92
		303.0	305.0	2.0	1.18	22.86
		306.0	343.7	37.7		0.01
		343.7	344.5	0.8	0.51	1.65
		344.5	349.8	5.3		0.02
LIM-24-4962		0.0	24.3	24.3		0.01
		24.3	42.6	18.3		NS
		42.6	134.6	92.0		0.01
		134.6	135.5	1.0		14.55
		135.5	164.2	28.7		0.06
		164.2	164.7	0.5		0.53
		164.7	172.6	7.9		0.04
		172.6	173.0	0.5		0.45
		173.0	198.4	25.4		0.05
		198.4	203.4	5.0		0.54
		203.4	207.3	3.9		0.10
		207.3	217.0	9.8		3.25
	<i>Including</i>	209.1	210.3	1.2		23.60

		217.0	274.6	57.6		0.05
		274.6	276.6	2.1		0.65
		276.6	283.5	6.9		0.12
		283.5	294.0	10.5		NS
		294.0	300.1	6.2		0.05
		300.1	308.6	8.5		0.30
		308.6	315.4	6.8		1.70
	<i>Including</i>	<i>308.6</i>	<i>309.8</i>	<i>1.2</i>		<i>7.48</i>
		315.4	369.8	54.4		0.05
		369.8	379.6	9.9		0.23
		379.6	381.0	1.4		1.23
		381.0	383.0	2.0		0.11
		383.0	383.9	1.0		2.72
		383.9	397.7	13.8		0.34
		397.7	460.4	62.7		0.04
LIM-24-4966		0.0	44.6	44.6		NS
		44.6	49.7	5.1		0.01
		49.7	65.0	15.4		NS
		65.0	82.5	17.5		0.01
		82.5	183.9	101.4		NS
		183.9	196.5	12.6		0.05
		196.5	262.8	66.3		NS
		262.8	273.2	10.4		0.04
		273.2	278.1	4.9		13.26
	<i>Including</i>	<i>274.1</i>	<i>275.2</i>	<i>1.2</i>		<i>33.50</i>
		278.1	280.4	2.3		0.11
		280.4	281.9	1.6		0.53
		281.9	284.1	2.2		0.08
		284.1	288.0	3.9		0.48
		288.0	341.4	53.4		0.05
LIM-24-4946		0.0	26.6	26.6		NS
		26.6	67.6	41.0		0.00
		67.6	83.6	16.0		NS
		83.6	91.1	7.5		0.00
		91.1	93.3	2.2		0.97
		93.3	101.7	8.4		0.12
		101.7	125.3	23.6		1.85
	<i>Including</i>	<i>101.7</i>	<i>103.6</i>	<i>1.9</i>		<i>3.34</i>
		112.3	117.0	4.7		5.86
		125.3	140.2	14.9		NS
		140.2	148.5	8.4		0.08
		148.5	150.7	2.2		1.12
		150.7	163.3	12.6		0.01

		163.3	164.9	1.6		1.11
		164.9	173.0	8.2		0.07
		173.0	178.3	5.3		4.50
	<i>Including</i>	173.8	175.6	1.8		12.50
		178.3	193.5	15.2		0.09
		193.5	210.2	16.7		NS
		210.2	213.5	3.4		0.92
		213.5	236.9	23.4		0.05
		236.9	237.4	0.5		0.95
		237.4	264.0	26.6		0.02
		264.0	264.8	0.8		0.41
		264.8	297.2	32.5		0.02
		297.2	323.2	26.0		NS
		323.2	361.1	38.0		0.01

Note: Estimated True Widths ('ETW') for reported vein intercepts are based on 3D models of the individual veins. Estimates are determined in cross-section by measuring the modelled vein thickness perpendicular to the vein margins and through the midpoint of the drill hole intercept. Percentage based differences between individual ETW's and down-hole interval lengths will vary between drill holes depending on drill hole inclination, variations in vein strike and dip, and overall geometries of the different vein systems.

September 10, 2024 – Drill Hole Collar Coordinates

Drill Hole ID	UTM East (m)	UTM North (m)	Elevation (masl)	Total Depth (m)	Azimuth (degrees)	Dip (degrees)
LIM-24-4890	532161.441	1408134.403	78.01	160	80	-75
LIM-24-4895	531894.503	1409195.095	67.129	120.05	205.05	-50.53
LIM-24-4917	533190.398	1410118.689	53.375	203.9	304.38	-49.19
LIM-24-4933	538499.507	1409309.825	60.394	131	260.29	-60.96
LIM-24-4937	532136.95	1408118.423	70.431	360	290	-71
LIM-24-4938	531330.718	1410264.044	82.236	159.9	286.02	-55
LIM-24-4939	538387.383	1409384.042	65.81	76	260	-50
LIM-24-4943	524080	1409494	61.815	449.85	146.76	-66.01
LIM-24-4945	532241.263	1407998.001	82.421	350	275	-73
LIM-24-4946	531263.356	1410072.965	76.048	367.35	265.74	-55.17
LIM-24-4953	523990.211	1409848.658	57.933	571.65	178.29	-48.47
LIM-24-4962	524292	1409672	68.345	466.5	200	-50
LIM-24-4966	530783.843	1410557.67	109.881	341.35	242.09	-49.83